



Positive Battery Post Relocation Kit

This sheet must be read completely to:

1. Provide assistance/clarification to the installer, customer, end user or others.
2. Avoid causing injury or death to installer, customer, end user, or others.
3. Prevent damage to vehicle and/or accessory or other.

HEY YOU! Please, please, please read the instructions completely prior to installation. 90% of questions we receive could be answered simply by reading ALL the instructions before installing anything. If you have any question or problem during the installation, please contact us as necessary. Phone support will always provide the quickest response. Installation of this product implies your agreement with our sales, warranty, exchange and return policies found on our website.

You can thank the lawyers for this next bit of fun. With that said, lets go!

Installer: Pretty please, give this sheet to the customer after reading it.

It is virtually impossible for us to be able to address every possible situation an installer or user will encounter. This requires both to exercise due dilligence and to apply some level of common sense. AKA...no 'hold my beer and watch this' type stuff.

Important Information in our instructions will be provided in the following manner:

SHOP TIP: literally great info we have gathered from hands-on installs or customer feedback.

NOTE: important information regarding the installation. Pay attention.

CAUTION: failure to follow instructions could result in damage to vehicle and/or accessory. Really pay attention.

WARNING: failure to follow instructions could result in injury/death of operator and/or passenger/others. For Pete's sake, PAY ATTENTION!

NOTE:

1. "Left", "Right", "Front" and "Rear" are described from the seated position of the vehicle. Vroom vroom.
2. Check local laws regarding the use of auxiliary lighting and electronics. Don't be 'that guy'.
3. Use of owners manual or service manual is recommended for installation. Sorry....more reading.
4. If so equipped, place motorcycle on it's centerstand on solid, level ground or engage parking brake. Do it like Mom is watching.

CAUTION:

1. When adding electrical accessories, always disconnect the battery and properly fuse new electronics.
2. DO NOT let the smoke out of the part. All electronics operate on smoke....when released, electronics are dead.

WARNING:

1. Allow the vehicle to cool prior to installation & when operating engine, allow adequate ventillation. Yep.
2. NEVER modify the kit in ANY manner. Doing so voids warranty and places all liability on the installer and/or user. Nope.
3. Never route wires or install components that interfere with the operation of the steering, suspension, brake/clutch/gas lever/pedal/grip or any other operational function of the vehicle. Duh.
4. Never allow your accessories to cause distractions to remove your focus off the vehicles operation. Never forget that this is a high risk sport - don't make it a higher risk when you don't have to. Major duh.
5. Never allow your accessories to cause distractions to others on the road. Super sized duh.

Part Listing

- 1 copper post assembly
- 1 plastic cover
- 1 6x25mm flange bolt
- 1 9/32"x3/8"x5/8"od steel spacer
- 1 post hardware kit (flat & lock washer, nut).

Tools / Supplies Required

- 10mm socket
- 14mm socket (post).

Note: this kit was designed using a stock OEM type battery. Some aftermarket batteries may not have the same post type, offset, or thread size.

1. Remove your sidecover.
2. Remove the bolt holding the positive cable to the battery.
3. Place the bolt through the hole in the hole in the copper post assembly.
4. Place the spacer over threads.
5. Insert the bolt threads into the OEM battery cable and post.

Caution: use care to NOT touch any metal with your socket in the next step.

6. 2018+ Goldwings.
Place the unit straight up and down as shown in the picture.

Pre-2018 Goldwings.

Place the unit at an angle as shown in the picture. Note that you will have to notch the black plastic cover that is held in place with a pushpin or remove it. Orientation may vary based on any added accessories.

Tighten the bolt using a socket.

7. Add any additional wires to the new post as needed.
8. Snap the cover into place. Reassemble the motorcycle.

2018+ orientation



pre-2018 orientation

