



## Installation Instructions For Part 45-8907C GL1500 FRONT FENDER EXTENSION

**NOTE: Read Instructions thoroughly before installing. Insure bike is stabilized before starting the installation.**

**ITEMS NEEDED:** Small Straight Blade Screwdriver  
#3Phillips Screwdriver  
5MM, 6MM Allen Wrench  
8MM, 10MM wrench  
1/4 Inch drill bit and electric drill  
Center punch and hammer

1. Remove items as shown using straight blade screwdriver. Pry off the two fork cover caps and with a 5mm allen wrench, unfasten the two bolts (Figure 1A). Remove fork cover.
  - a. Pull outward and forward to remove left hand side covers. (Figure 1B)
  - b. Using 8mm and 10mm wrenches, remove the three bolts from the left hand disc cover. Repeat for right side disc cover. (Note for re-installation; the top 10mm bolts (Figure 1C) do not have collars included.)
  - c. Using the Phillips screwdriver, unfasten speedometer cable (figure 1D)
  - d. Using the 8mm wrench, remove the left hand side fender bolts (figure 1E)
  - e. Using the 8mm allen wrench, remove the four top bolts (figure 1F) from the fork stay bracket, and remove bracket.
2. With the rear fender off the motorcycle, hold front fender extension in place and using center punch and hammer, light tap the three drilling locations (figure A). Set the fender extension aside and drill three 1/4 inch holes at marked locations (figure B).
3. Attach fender extension to fender with hardware provided (figure 3).
4. Re-install all items previously removed in step 1.

