




GOLDSTRIKE SPEAKER GRILLS

GOLDSTRIKE
A DIVISION OF CIRO

INSTALLATION INSTRUCTIONS:

1. Park on a level surface and shut off the motorcycle. Lift motorcycle onto its center stand if available. Ensure the engine has time to cool before installation.
2. Clean the left and right speaker surround with hot water and soap to remove all dirt and debris.
3. ATTENTION: Thoroughly clean the mounting surfaces with denatured alcohol to remove all wax, oil, and residue.
NOTE: New motorcycles are delivered from the factory covered in protective oil. Remove it before installing this product.
NOTE: Do not install if the temperature is below 50° F. The adhesive will not cure properly.



4. Test fit the Speaker Grills to familiarize yourself with their location. Take note where the 3M VHB tape is located on the back of the Speaker Grills.
5. Apply the adhesion promoter to both left and right speaker surrounds following the directions on the package. Apply the promoter where the 3M VHB tape will come into contact with the speaker surround.
6. Peel off the adhesive liner from the 3M VHB tape on the back of the Speaker Grill and press it onto the speaker surround.

Goldstrike3D.com

G0078350, REV. -

Parts Included:	1	Left Speaker Grill
	1	Right Speaker Grill

WARNING:

This indication alerts you to the fact that ignoring the contents described herein can result in potential serious injury or death if not followed.

CAUTION:

This indication alerts you to the fact that ignoring the contents described herein can or will result in material damage and/or personal injury.

ATTENTION:

This indication alerts you to the fact if you ignore this detail you will affect the performance or functionality of the product.

All Ciro products are designed for "easy assembly" and/or "plug and play". We recommend a competent mechanic install our products, using standard mechanical procedures to assure a safe and successful installation.

NOTE:

Ciro products are designed and manufactured under very strict quality control. Ciro warrants that products sold to the original purchaser shall be free from any defects in materials and workmanship for a period of 3 (three) years from the date of purchase, and a lifetime warranty against LED failure.

Ciro will have no obligation if the customer cannot show proof of purchase.

Warranty will not be granted unless the part is properly installed and maintained.

Ciro will not be liable for any consequential and incidental damages, including labor, or non-Ciro products.

Please visit our website Ciro3d.com for our complete warranty policy.