



TRICEPTOR FENDER ACCENT

7340

HONDA: ALL '01-UP GL1800, VTX1800 AND 1300
YAMAHA: ALL V-STAR 1300, 1100 AND 650, ALL '99-UP ROAD STAR, ALL ROADLINER AND STRATOLINER
UNIVERSAL: 4" OR WIDER STYLE FENDERS (DOES NOT FIT FENDERS WITH FLAT CENTER WIDTH)

PARTS INCLUDED

- 1 Triceptor Fender Accent
- 1 Alcohol Pad
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

CAUTION! Ensure that the installation of this product does not interfere with the proper operation of the motorcycle before riding.

ATTENTION! Be sure the area is free of grease, oil, dirt, or other debris to ensure proper adhesion. Kuryakyn WILL NOT warranty any parts lost due to improper installation.

ATTENTION! The adhesive may not correctly bond if applied at temperatures less than 50°F. Do not attempt this installation in temperatures less than 50°F.

NOTE Installation is shown on a VTX1800F; while representative of typical procedure, there may be minor differences when installed on other models.

NOTE Before you install the Triceptor Fender Accent, determine your preferred mounting location. Suggested mounting locations are shown in PIC.1.

NOTE Remove the locating tabs with a pair of needle nose pliers, if necessary, for proper fit. Bend the tabs back and forth until they release; carefully cut the remaining tab base until it is flush with a razor blade.

NOTE The Triceptor Fender Accent was designed to flex and bend to follow the contour of a fender. Ensure that the entire piece is pressed into place.

TOOLS SUGGESTED

Soapy water and clean rag.

PROCEDURE

STEP 1 Clean the mounting location thoroughly with soapy water and a clean rag.

PIC.1



STEP 2 Clean the mounting location with the included Alcohol Pad and allow to dry completely.

-cont.-

CUSTOMER SERVICE

877.370.3604 (toll free)

INSTALLATION QUESTIONS

techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today—select the "CATALOGS" icon. Each Kuryakyn product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA All Rights reserved.



STEP 3 Rub the adhesive backing to activate the adhesive. See [PIC.2](#).

STEP 4 Remove the adhesive backing.

STEP 5 Position the Triceptor Fender Accent on the fender and press down on the entire piece for at least 60 seconds for the best adhesion. Full bond strength will occur within 24 hours.

NOTE Press the center of the Triceptor Fender Accent into place first and then the outsides to ensure full adhesive bond.

Ride On!

Kuryakyn

PIC.2



PAGE

2

TRICEPTOR FENDER ACCENT

INSTALLATION