

Copyright © 2017 by Big Bike Parts, Inc. No part of this instruction sheet may be reproduced without the written permission of Big Bike Parts, Inc.

PART NO. 4-248A

12" FLAG POLE WITH 1/2" ROUND CLAMP

FITMENT:

FITS 1/2" ROUND TUBE RACKS AND RAILS

8/4/2017

TOOLS NEEDED: PHILLIPS SCREWDRIVER

9/16" WRENCH

1/8" ALLEN WRENCH

THREAD LOCK

**PLEASE READ THROUGH AND UNDERSTAND THESE INSTRUCTIONS BEFORE BEGINNING.****ESTIMATED INSTALLATION TIME: 10 TO 15 MIN.****INSTALLATION:**

1. USING A 9/16" WRENCH REMOVE THE HEX NUT AND THE LOCK WASHER FROM THE BOTTOM THE FLAG POLE.
2. REMOVE THE CLAMPS FROM THE MAST.
3. USING A PHILLIPS SCREW DRIVER LOOSEN THE 1/4" SCREW HOLDING THE TOP AND BOTTOM CLAMP TOGETHER.
4. PLACE THE CLAMPS ON THE 1/2" ROUND MOUNTING SURFACE.
5. WRAP THE RUBBER SPACER AROUND THE 1/2" MOUNTING SURFACE AND POSITION THE CLAMPS OVER THE RUBBER SPACER.
6. USING A PHILLIPS SCREWDRIVER TIGHTEN THE 1/4" SCREW.
7. INSERT THE MAST THROUGH THE TOP OF THE TOP CLAMP AND REINSTALL THE LOCK WASHER AND HEX NUT ON THE BOTTOM OF THE MAST.
8. POSITION THE MAST AS DESIRED AND USING A 9/16" WRENCH TIGHTEN THE NUT ON THE BOTTOM OF THE MAST.
9. UNSCREW THE TOPPER FROM THE TOP OF THE MAST.
10. REMOVE THE SET SCREW AND PLACE A DROP OF THREAD LOCK ON THE SET SCREW. REINSTALL THE SET SCREW AND TIGHTEN INTO THE TOPPER.
11. SLIDE THE O-RING OVER THE TOP OF THE MAST AND POSITION IT ABOUT 6" FROM THE TOP OF THE MAST.
12. SLIDE THE FLAG OVER THE TOP OF THE MAST AND REINSTALL THE TOPPER.

