



# Goldstrike Action Camera Mount

## Parts Included:

1	Camera ball mount	1	Collet nut
1	Spacer	1	M5 Nylon insert lock nut
1	Flat washer	1	M5 x .8 x 20mm BSCS
1	M5 x 35mm BSCS	1	Camera adapter

## Installation Instructions:

1. Park on a level surface and shut off the motorcycle. Ensure that the engine has had time to cool before installation.
2. Decide if camera will be mounted to the left or right side of the motorcycle. Remove existing screw from below mirror. Screw will not be re-used. (Fig. 1)



3. Install M5 x 35mm BSCS with flat washer into camera ball mount. Place spacer onto screw (small stepped end of spacer toward motorcycle). (Fig. 2)

4. Loosely install camera ball mount onto the motorcycle (thread locking fluid is recommended).



5. Attach camera (not included) to camera adapter using the M5 x 20mm BSCS and lock nut or the hardware supplied with camera. (Fig. 3)

6. Slide the collet nut over the ball mount and carefully snap the camera adapter onto the ball mount. Thread collet nut into position, adjusting the camera mount position as needed. Be sure to maintain clearance with the motorcycle and adjust camera for the preferred angle. You may need to reference your camera's documentation for rotation/orientation settings.

7. Once a suitable position is found, tighten all hardware securely. Tighten the motorcycle's attachment screw to 5.2 N-m (3.8 ft-lbs) The collet nut on the ball should be hand-tightened. Note: To adjust camera adapter angle, loosen collet prior to moving. To remove camera from the motorcycle; loosen the collet nut fully from the threads and pull adapter from ball mount. Be sure to keep camera adapter and collet nut in a secure location. The ball mount can remain on the motorcycle.

## WARNING:

This indication alerts you to the fact that ignoring the contents described herein can result in potential serious injury or death if not followed.

## CAUTION:

This indication alerts you to the fact that ignoring the contents described herein can or will result in material damage and/or personal injury.

## ATTENTION:

This indication alerts you to the fact if you ignore this detail you will affect the performance or functionality of the product.

All Ciro products are designed for "easy assembly" and/or "plug and play". We recommend a competent mechanic install our products, using standard mechanical procedures to assure a safe and successful installation.

## NOTE:

Ciro products are designed and manufactured under very strict quality control. Ciro warrants that products sold to the original purchaser shall be free from any defects in materials and workmanship for a period of 3 (three) years from the date of purchase, and a lifetime warranty against LED failure.

Ciro will have no obligation if the customer cannot show proof of purchase.

Warranty will not be granted unless the part is properly installed and maintained.

Ciro will not be liable for any consequential and incidental damages, including labor, or non-Ciro products.

Please visit our website [Ciro3d.com](http://Ciro3d.com) for our complete warranty policy.