

CIRO ACCESSORY PERCH MOUNT

Parts included:

- 1 Ciro Accessory Perch Mount
- 1 Hardware Kit Including:
 - 1/4-20 x 1-3/4" Bolts 2
 - 1/4-20 x 2" Bolts
 - M6 x 50mm Bolbs
 - 2 Spacers

Installation Instructions:

- Park on a level surface and shub off the bike. Ensure that the engine has had time to cool before installation. Cover your tank with a clean towel or blanket to protect it.
- 2. Remove the two perch bolts with a T27 Torx on the side that you would like your perch mount. Be careful not to let your controls fall on the tank.



- 3. Compare the threads of your old bolts to the bolts supplied in the kit. The shorter 1/4-20's are commonly used in newer Harley models. Use the M6 for metric bikes. Prepare the perch mount as shown above.
- 4. Use a 3/16" allen to install the perch mount in the location of the removed torx bolts, as shown to the right.
- 5. You may use a 5/32" allen to loosen the small bolt on top of the mount to adjust the position of the ball.
- *If you have purchased any Ciro accessories to go with your ball mount, please refer to those

instructions to complete your installation.

This indication alerts you to the fact that ignoring the contents described herein can result in potential serious injury or death if not followed.

CAUTION:

WARNING:

This indication alerts you to the fact that ignoring the contents described herein can or will result in material damage and/or personal injury.

ATTENTION:

This indication alerts you to the fact if you ignore this detail you will affect the performance or funcbionality of the product.

All Cira products are designed for "easy assembly" and/or "plug and play". We recommend a competent mechanic install our products. using standard mechanical procedures to assure a safe and successful installation.

NOTE:

Ciro products are designed and manufactured under very strict quality control. Ciro products are warranted to be free of defects in material and workmanship for 1 (one) year from date of purchase by the consumer.

Ciro will have no obligation if the customer cannot show proof of ourchase.

Warranty will not be granted unless the part is properly installed and maintained.

Ciro will not be liable for any consequential and incidental damages, including labor, or non-Ciro prod-

Please visit our website Ciro3d.com for our complete warranty policy.

CIRO3D.COM